



LUMINAIRE SPECIFICATIONS

MANUFACTURER: KING LUMINAIRE
 STYLE: AURORA SR.
 LIGHT SOURCE: LED
 SERIES: 8060
 OPTICAL SYSTEM: P4FL
 IES CLASSIFICATION: TYPE III
 WATTAGE: 100W
 VOLTAGE: 120-277V
 CCT: 3000K
 FINISH: TGIC POLYESTER POWDERCOAT, FED. STD. #17038 GLOSS BLACK
 OPTIONS: • KPL20-PR7 PLUMIZER w/ CONTROLLER
 CATALOG NO.: K829-P4FL-III-100(SSL)-8060-120V-3K-BK

POLE SPECIFICATIONS

MANUFACTURER: HAPCO POLES
 POLE:
 STYLE: 16 SHARP FLUTE, ROUND TAPERED ALUMINUM
 HEIGHT: 25'-0"
 POLE BUTT: Ø8"
 POLE TOP: Ø4 1/2"
 MATERIAL: ALUMINUM, .188 WALL THICKNESS
 HAND HOLE: 4" x 6"
 ANCHOR BOLTS: (4) Ø1" x 36"L + 4" LEG, F1554-Gr55 HD GALV.
 BOLT CIRCLE: Ø11-12"
 BOLT PROJ.: 4"
 TENON SIZE: Ø2 3/8" x 2 3/4"L
 OPTIONS: • INTERNAL VIBRATION DAMPER
 • GFCI 20AMP OUTLET w/ WP COVER
 BASE:
 STYLE: ARLEN 24 (2-PIECE CLAMSHELL)
 HEIGHT: 32"
 WIDTH: Ø24"
 MATERIAL: CAST ALUM. ALLOY 319
 FINISH: TGIC POLYESTER POWDERCOAT, FED. STD. #17038, GLOSS BLACK
 CATALOG NO.: A4C25D8-4-TF16-BA-TENON-GFI-V

CROSS ARM SPECIFICATIONS

MANUFACTURER: KING LUMINAIRE
 STYLE: KA30
 RISE: 24"
 LENGTH: 72"
 MATERIAL: ALUMINUM
 FINISH: TGIC POLYESTER POWDERCOAT, FED. STD. #17038 GLOSS BLACK
 CATALOG NO.: KA30-T-1-6'

